

# ANSI/CEA Standard

Loudspeakers, Optimum Amplifier  
Power

ANSI/CEA-426-B R-2005

July 1998



**CEA**<sup>®</sup>  
Consumer Electronics Association  
[www.CE.org](http://www.CE.org)

## NOTICE

Consumer Electronics Association (CEA<sup>®</sup>) Standards, Bulletins and other technical publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards, Bulletins and other technical publications shall not in any respect preclude any member or nonmember of CEA from manufacturing or selling products not conforming to such Standards, Bulletins or other technical publications, nor shall the existence of such Standards, Bulletins and other technical publications preclude their voluntary use by those other than CEA members, whether the standard is to be used either domestically or internationally.

Standards, Bulletins and other technical publications are adopted by CEA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, CEA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard, Bulletin or other technical publication.

This CEA Standard is considered to have International Standardization implication, but the International Electrotechnical Commission activity has not progressed to the point where a valid comparison between the CEA Standard and the IEC document can be made.

This Standard does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

(Formulated under the cognizance of the CEA's **R3 Audio Systems Committee**.)

Published by

©CONSUMER ELECTRONICS ASSOCIATION 1998  
Technology & Standards Department  
1919 S. Eads Street  
Arlington, Virginia 22202

**PRICE: Please call Information Handling Services, USA and Canada (1-800-854-7179)  
International (303-397-7956), or  
<http://global.ihs.com>  
All rights reserved  
Printed in U.S.A.**

PLEASE!

DON'T VIOLATE  
THE  
LAW!

This document is copyrighted by the Consumer Electronics Association (CEA<sup>®</sup>)  
and may not be reproduced without permission.

Organizations may obtain permission to reproduce a limited number of copies by  
entering into a license agreement. For information contact:

Information Handling Services  
15 Inverness Way East  
Englewood, Colorado 80112-5704  
or call U.S.A. and Canada 1-800-854-7179, International (303) 397-7956  
See <http://global.ihs.com> or email [global@ihs.com](mailto:global@ihs.com)



# Loudspeakers, Optimum Amplifier Power

## Contents

1	Foreword .....	1
2	Introduction .....	1
3	Title .....	2
4	Scope .....	2
5	Normative references .....	2
6	Definitions .....	3
7	Test methods .....	3
7.1	Apparatus .....	3
7.2	Test conditions and operator notes .....	3
7.3	Section A—Power compression .....	4
7.4	Section B—Distortion .....	5
7.5	Section C—Accelerated life test at continuous power .....	5
8	Marking, labeling, packaging .....	6
	Annex A (normative) .....	6
A.1	Test CD description .....	7
A.2	Amplitude calibration .....	7
A.3	Variable rate sweep test signal .....	7
A.4	Distortion test signals .....	8
A.5	Accelerated life test signal .....	8
	Annex B (normative) .....	11
B.1	Equipment block diagram .....	11
B.2.	Test baffle for unmounted speakers .....	11
	Annex C (informative) .....	12

Figures

1	Graph of signal spectrum .....	9
2	Clipper circuit example .....	10
3	Block diagram.....	11
4	Example of circuit for measuring voice coil temperature .....	13

# Loudspeakers, Optimum Amplifier Power

## 1 Foreword

**1.1** This standard was developed by the CEA R-3 Audio Systems Committee working group for study and revision of CEA-426-A, in response to a survey of loudspeaker manufacturers which indicated a need to re-examine the current standard in the areas of test signal spectrum, test duration, and the calculation of power. CEA-426-A comprises an "accelerated life" test of full-range systems.

**1.2** This document extends 426-A to include standards for performance with respect to power compression and distortion at the optimum amplifier power, and provides for a test signal contained on a compact disc, to improve test reliability and to facilitate and encourage wider use of the standard. The procedures are organized in three sections: Section A contains the procedure for testing power compression, Section B contains the procedure for testing distortion, and Section C contains the procedure for the accelerated life test. The *optimum amplifier power* is the maximum input power at which the product under test is rated to meet the stated CEA criteria for acceptability under all three limit categories — power compression, distortion, and accelerated life.

**1.3** Whereas CEA-426-A rated the ability of a loudspeaker to handle power — a concept of little practical use — the revised standard, CEA-426-B, recommends the maximum power rating for an amplifier to be connected to the loudspeaker. This could be considered an "optimum" power match, as this is the most power which can be delivered to the speaker while permitting the speaker to operate within acceptable limits of performance as defined by CEA in this standard under the categories of power compression, distortion, and accelerated life testing.

## 2 Introduction

**2.1** The present standard specifies a test signal generated by applying a shaping filter to a random noise source and diode-clipping the signal to a 6 dB crest factor. In a study of this signal, new data suggested that the signal spectrum should contain a greater amount of energy in the mid-bass and treble regions. Therefore, a new spectrum shape has been created. To improve the consistency and convenience of the standard, test signals with the new spectrum have been recorded on compact disc along with other test signals for distribution through the CEA. Power calculation is made simple through the use of a calibrated test tone recorded on the compact disc. A complete description of the test signals used in all three tests is found in Annex A (normative).

**2.2** The input voltage for the accelerated life test is specified to be 3 dB lower than for the power compression and distortion tests for the same power rating amplifier power recommendation, as the crest factor of the weighted compressed noise test signal is 3 dB higher than that of the sine wave used for these other tests.